



## Use and Care Instructions

### Maintenance

After your ClearVue Railing Systems has been up for about six months, we recommend that you check the tightness of the bolts.

### Cleaning Your ClearVue Railing Systems

To keep your ClearVue Railing Systems clear and looking like new wash it occasionally with soap and water. Use the pole mounted 100% cotton wash pad and non-abrasive dish soap (Joy Liquid is fine) or non-abrasive car wash solution. Wash like you would a car, first hosing off loose dirt. Wash the surface with 100% cotton pad, using plenty of sudsy water and rinsing the pad frequently.

In high pollen and high rain areas you may experience algae buildup in the spring. Use a bleach solution of 1 cup/gallon of water and a small cotton towel to remove the algae. Rinse thoroughly and let it air dry. If you have hard water that leaves water spots you can dry it with a 100% cotton terry towel.

Wash the underside of it same way. You can dry the underside with a soft 100% cotton towel to remove water spots. For tree sap and other non-water soluble compounds use VM&P Naphtha.

### Enhancing the Optical Clarity

A yearly application of polish will keep your ClearVue Railing Systems brilliantly clear. Most owners rarely polish their ClearVue Railing Systems but if you would like to keep your enclosure absolutely pristine, you can use any of the following polishes: Meguiar's #18 One Step Plastic Polish, Meguiar's #17 Clear Plastic Cleaner, Meguiar's #10 Clear Plastic Polish, Rain Dance Car Wax, and Plexus Plastic Polish.

### Removing Scratches

Polycarbonate is a resilient material but it can get scratched by a hard, sharp object. Be sure to wash the ClearVue Railing Systems before removing the scratch.

First, try using one of the polishing products listed in the previous section. If the scratch remains and you would like to work on it further, use a mild abrasive compound such as auto rubbing compound or Brasso.

Apply the rubbing compound or Brasso to a small piece of cloth and rub in the direction of the scratch. Follow with an application of Meguiar's #17 and #10.

For deep scratches and gouges use the same materials and techniques as used for fixing blemishes in auto paint. Use two or three steps of finer and finer abrasive treatment to polish out the scratch.

### Panel Replacement

If a panel becomes severely damaged, it can be replaced. Please contact your dealer or Hansen Architectural Systems for information on replacing a panel.

### ClearVue Railing Systems Care "Do's"

- Wash dirt and debris from the surface using plenty of water.
- In areas of high pollen, wash your ClearVue Railing Systems in the spring to keep it looking clear.
- Use only 100% cotton deep-pile terry towels to clean and dry your ClearVue Railing Systems.
- It is safe to use the following cleaning products: Meguiar's Soft Wash Gel, Joy, Top Job, Palmolive Liquid, Mr. Clean, Windex with Ammonia D, and typical car wash liquids.

### ClearVue Railing Systems Care "Don'ts"

- Do not wipe dirt from the surface with a dry cloth.
- Never sweep debris off the top with a broom.
- Do not remove snow using a broom or brush.
- Do not use paper towels, diapers, dish-cloths, or brushes to clean the surface.
- The following products are not approved for use on polycarbonate: Armor-All, Butyl Cellosolve, Formula 409, Lysol, Pinesol.

### Questions?

If you have questions or encounter a problem, please contact the dealer where you bought your SkyVue Railings Systems or call Hansen Architectural Systems, Inc. at 1-800-599-2965, or e-mail us at [info@aluminumrailing.com](mailto:info@aluminumrailing.com)